

# 屋内照明器具特性

|         |                |          |
|---------|----------------|----------|
| 品番 (品名) | LGB16700       |          |
| 光源      | LLD3020CU1 ×1  | 615.0 lm |
| 管理番号    | K0178740(0)DR1 |          |
| BZ分類    | BZ1            |          |

|        |             |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    |     |    |    |    |
|--------|-------------|-----------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|-----|----|----|----|
| 器具効率   | 54%         | 天井              | 80%  |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |     |    | 0% |    |
|        | 上方光束        |                 | 0%   | 壁  | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70 | 50 | 30  | 10 | 70  | 50 | 30 | 10 |
| 下方光束   | 54%         | 床               | 10%  |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |     |    | 0% |    |
| 室指数    | 照明率 (X0.01) |                 |      |    |    |    |     |    |    |    |     |    |    |    |     |    | ZCM |    |    |    |
| 保守率    | 良           | 0.67            | 0.6  | 43 | 40 | 38 | 36  | 43 | 40 | 38 | 36  | 42 | 39 | 37 | 36  | 42 | 39  | 37 | 36 | 35 |
|        | 中           | 0.63            | 0.8  | 47 | 44 | 41 | 40  | 46 | 43 | 41 | 40  | 45 | 43 | 41 | 40  | 45 | 42  | 41 | 40 | 39 |
|        | 否           | 0.56            | 1.0  | 49 | 46 | 44 | 42  | 48 | 46 | 44 | 42  | 47 | 45 | 43 | 42  | 47 | 45  | 43 | 42 | 41 |
| 下方投影面積 | 等価発光面積      | cm <sup>2</sup> | 1.25 | 51 | 48 | 46 | 45  | 50 | 48 | 46 | 45  | 49 | 47 | 45 | 44  | 48 | 46  | 45 | 44 | 43 |
|        |             |                 | 1.5  | 52 | 50 | 48 | 46  | 51 | 49 | 47 | 46  | 50 | 48 | 47 | 46  | 49 | 48  | 46 | 45 | 45 |
| 取付高さ   | 器具間隔最大限     |                 | 2.5  | 54 | 53 | 51 | 50  | 54 | 52 | 51 | 50  | 53 | 51 | 50 | 49  | 51 | 50  | 50 | 49 | 48 |
|        | 横方向 (A)     | 縦方向 (B)         | 3.0  | 55 | 53 | 52 | 51  | 54 | 53 | 52 | 51  | 53 | 52 | 51 | 50  | 52 | 51  | 50 | 50 | 49 |
| Hm     | 0.49Hm      | 0.49Hm          | 4.0  | 56 | 55 | 54 | 53  | 55 | 54 | 53 | 52  | 54 | 53 | 52 | 52  | 53 | 52  | 51 | 51 | 50 |
|        |             |                 | 5.0  | 56 | 55 | 54 | 54  | 55 | 55 | 54 | 53  | 54 | 54 | 53 | 52  | 53 | 53  | 52 | 52 | 52 |
|        |             |                 | 7.0  | 57 | 56 | 55 | 55  | 56 | 55 | 55 | 54  | 55 | 54 | 54 | 53  | 54 | 53  | 53 | 53 | 51 |
|        |             |                 | 10.0 | 57 | 57 | 56 | 56  | 56 | 56 | 55 | 55  | 55 | 55 | 54 | 54  | 54 | 54  | 53 | 53 | 52 |

