

屋内照明器具特性

品番 (品名)	LGB16701															
光源	LLD3000CU1 x1 795.0 lm															
管理番号	K0178742(0)DR1															
BZ分類	BZ4/6.0/BZ5															

器具効率	53%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	2% 51%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	31	25	22	19	31	25	21	19	29	24	21	19	28	24	21	19	17		
		0.8	36	31	27	24	35	30	26	24	34	29	26	24	33	29	26	23	22		
		1.0	40	34	30	27	39	34	30	27	37	33	30	27	35	32	29	27	25		
		1.25	42	38	34	31	42	37	34	31	40	36	33	31	38	35	32	30	29		
下方投影面積 等価発光面積	c m ² c m ²	1.5	44	40	37	34	44	39	36	34	42	38	36	33	40	37	35	33	31		
		2.0	47	44	41	38	46	43	40	38	45	42	39	37	43	40	38	37	35		
取付 高さ	器具間隔最大限		2.5	49	46	43	41	48	45	43	41	46	44	42	40	45	43	41	39	38	
	横方向 (A) H m	縦方向 (B) H m	3.0	50	47	45	43	49	47	45	43	48	45	44	42	46	44	43	41	39	
			4.0	52	50	48	46	51	49	47	45	49	47	46	45	48	46	45	44	42	
			5.0	53	51	49	48	52	50	49	47	50	49	47	46	49	47	46	45	44	
			7.0	54	52	51	50	53	52	51	49	51	50	49	48	50	49	48	47	46	
			10.0	55	54	53	52	54	53	52	51	52	52	51	50	51	50	50	49	47	

