

屋内照明器具特性

品番 (品名)	LGB16701															
光源	LLD3000CU1 x1 795.0 lm															
管理番号	K0178742(0)DR1															
BZ分類	BZ4/6.0/BZ5															

器具効率	53%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	2% 51%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	31	25	22	19	31	25	21	19	29	24	21	19	28	24	21	19	17		
		0.8	36	31	27	24	35	30	26	24	34	29	26	24	33	29	26	23	22		
		1.0	40	34	30	27	39	34	30	27	37	33	30	27	35	32	29	27	25		
		1.25	42	38	34	31	42	37	34	31	40	36	33	31	38	35	32	30	29		
下方投影面積 等価発光面積	c m ² c m ²	1.5	44	40	37	34	44	39	36	34	42	38	36	33	40	37	35	33	31		
		2.0	47	44	41	38	46	43	40	38	45	42	39	37	43	40	38	37	35		
取付 高さ	器具間隔最大限		2.5	49	46	43	41	48	45	43	41	46	44	42	40	45	43	41	39	38	
	横方向 (A) 縦方向 (B)	3.0	50	47	45	43	49	47	45	43	48	45	44	42	46	44	43	41	39		
H m	0.96 H m	0.96 H m	4.0	52	50	48	46	51	49	47	45	49	47	46	45	48	46	45	44	42	
			5.0	53	51	49	48	52	50	49	47	50	49	47	46	49	47	46	45	44	
			7.0	54	52	51	50	53	52	51	49	51	50	49	48	50	49	48	47	46	
			10.0	55	54	53	52	54	53	52	51	52	52	51	50	51	50	50	49	47	

