

屋内照明器具特性

品番 (品名)	LGB16701														
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m														
管理番号	K0184437 (0) DR1														
BZ分類	BZ3/1.4/BZ4														

器具効率	40%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 (×0.01)															ZCM			
下方光束	38%																				
保守率	良 中 否	0.67	0.6	2.4	2.0	1.7	1.6	2.4	2.0	1.7	1.6	2.3	1.9	1.7	1.5	2.2	1.9	1.7	1.5	1.5	
		0.63	0.8	2.8	2.4	2.1	1.9	2.7	2.4	2.1	1.9	2.6	2.3	2.1	1.9	2.5	2.2	2.0	1.9	1.8	
			1.0	3.0	2.7	2.4	2.2	3.0	2.6	2.4	2.2	2.8	2.6	2.3	2.2	2.7	2.5	2.3	2.1	2.0	
		0.56	1.25	3.2	2.9	2.7	2.5	3.2	2.9	2.6	2.4	3.0	2.8	2.6	2.4	2.9	2.7	2.5	2.4	2.3	
下方投影面積	c m ²	1.5	3.4	3.1	2.8	2.6	3.3	3.0	2.8	2.6	3.2	2.9	2.8	2.6	3.1	2.9	2.7	2.6	2.5		
		2.0	3.6	3.3	3.1	2.9	3.5	3.3	3.1	2.9	3.4	3.2	3.0	2.9	3.3	3.1	2.9	2.8	2.7		
取付高さ	器具間隔最大限		2.5	3.7	3.5	3.3	3.1	3.6	3.4	3.3	3.1	3.5	3.3	3.2	3.0	3.4	3.2	3.1	3.0		
	横方向 (A)	縦方向 (B)	3.0	3.8	3.6	3.4	3.3	3.7	3.5	3.4	3.2	3.6	3.4	3.3	3.2	3.5	3.3	3.2	3.1		
H _m	0.95H _m	0.95H _m	4.0	3.9	3.7	3.6	3.5	3.8	3.7	3.6	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.3		
			5.0	4.0	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.5	3.6	3.6	3.5	3.4		
			7.0	4.0	3.9	3.8	3.8	4.0	3.9	3.8	3.7	3.8	3.8	3.7	3.6	3.7	3.7	3.6	3.5		
			10.0	4.1	4.0	3.9	3.9	4.0	4.0	3.9	3.8	3.9	3.8	3.8	3.7	3.8	3.7	3.7	3.5		

