

屋内照明器具特性

品番 (品名)	LGB16701				
光源	LLD40001CQ1 ×1 845.0 1 m				
管理番号	K0186484 (0) DR 1				
BZ分類	BZ5 / 0.7 / BZ4 / 2.3 / BZ5				

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		1 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		46 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	2.7	2.2	1.8	1.6	2.7	2.1	1.8	1.5	2.5	2.1	1.8	1.5	2.4	2.0	1.7	1.5	1.4	
	中	0.63	0.8	3.2	2.6	2.3	2.0	3.1	2.6	2.3	2.0	3.0	2.5	2.2	2.0	2.8	2.5	2.2	2.0	1.9	
	否	0.56	1.0	3.5	3.0	2.6	2.4	3.4	2.9	2.6	2.4	3.2	2.8	2.6	2.3	3.1	2.8	2.5	2.3	2.2	
			0.56	1.25	3.8	3.3	3.0	2.7	3.7	3.3	2.9	2.7	3.5	3.2	2.9	2.7	3.4	3.1	2.8	2.6	2.5
下方投影面積			c m ²																		
			c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	0.85 H m	0.85 H m	4.0	4.6	4.4	4.2	4.1	4.5	4.3	4.2	4.0	4.4	4.2	4.1	3.9	4.2	4.1	4.0	3.9	3.7	
			5.0	4.7	4.5	4.4	4.2	4.6	4.5	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.1	4.0	3.8	
			7.0	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.3	4.2	4.0	
			10.0	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.6	4.6	4.6	4.5	4.4	4.5	4.4	4.4	4.3	4.2	

