

屋内照明器具特性

品番 (品名)	LGB15107														
光源	LLD2000CU1 x1 566.0 lm														
管理番号	K0178727(0)DR1														
BZ分類	BZ5														

器具効率	67%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	2%																			
下方光束	65%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.67 中 0.63 否 0.56	0.6	38	30	25	22	37	30	25	21	35	29	24	21	34	28	24	21	19	
		0.8	45	37	32	28	44	37	32	28	42	35	31	28	40	34	30	27	26	
		1.0	49	42	37	33	48	41	37	33	46	40	36	32	44	39	35	32	30	
		1.25	53	47	42	38	52	46	41	38	49	44	40	37	47	43	39	37	35	
下方投影面積	c m ²	1.5	56	50	45	42	54	49	45	41	52	47	44	41	50	46	43	40	38	
		2.0	59	55	51	47	58	54	50	47	56	52	49	46	53	50	47	45	43	
取付高さ	器具間隔最大限		2.5	62	58	54	51	60	57	53	50	58	55	52	49	56	53	51	48	46
	横方向 (A)	縦方向 (B)	3.0	63	60	57	54	62	59	56	53	60	57	54	52	57	55	53	51	49
H m	0.82 H m	0.82 H m	4.0	65	62	60	58	64	61	59	57	62	60	57	56	60	58	56	54	52
			5.0	67	64	62	60	65	63	61	59	63	61	59	58	61	59	58	57	54
			7.0	68	66	65	63	67	65	64	62	65	63	62	61	62	61	60	59	57
			10.0	69	68	67	65	68	67	66	65	66	65	64	63	64	63	62	61	59

