

# 屋内照明器具特性

品番 (品名)	LGB15108	
光源	LLD4000MLCE1 ×1	845.0 l m
管理番号	K0176247 ( 0 ) DR 1	
BZ分類	BZ5 / 0.7 / BZ4 / 2.3 / BZ5	

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		1 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		46 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	2.7	2.2	1.8	1.6	2.7	2.1	1.8	1.5	2.5	2.1	1.8	1.5	2.4	2.0	1.7	1.5	1.4	
	中	0.63	0.8	3.2	2.6	2.3	2.0	3.1	2.6	2.3	2.0	3.0	2.5	2.2	2.0	2.8	2.5	2.2	2.0	1.9	
	否	0.56	1.0	3.5	3.0	2.6	2.4	3.4	2.9	2.6	2.4	3.2	2.8	2.6	2.3	3.1	2.8	2.5	2.3	2.2	
	下方投影面積	c m <sup>2</sup>		1.25	3.8	3.3	3.0	2.7	3.7	3.3	2.9	2.7	3.5	3.2	2.9	2.7	3.4	3.1	2.8	2.6	2.5
等価発光面積	c m <sup>2</sup>		1.5	3.9	3.5	3.2	3.0	3.9	3.5	3.2	2.9	3.7	3.4	3.1	2.9	3.5	3.3	3.0	2.9	2.7	
	c m <sup>2</sup>		2.0	4.2	3.9	3.6	3.4	4.1	3.8	3.5	3.3	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.2	3.1	
取付高さ	器具間隔最大限		2.5	4.4	4.1	3.8	3.6	4.3	4.0	3.8	3.6	4.1	3.9	3.7	3.5	3.9	3.8	3.6	3.4	3.3	
	横方向 (A)	縦方向 (B)	3.0	4.5	4.2	4.0	3.8	4.4	4.2	3.9	3.8	4.2	4.0	3.8	3.7	4.1	3.9	3.8	3.6	3.5	
H m	0.85 H m	0.85 H m	4.0	4.6	4.4	4.2	4.1	4.5	4.3	4.2	4.0	4.4	4.2	4.1	3.9	4.2	4.1	4.0	3.9	3.7	
			5.0	4.7	4.5	4.4	4.2	4.6	4.5	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.1	4.0	3.8	
			7.0	4.8	4.7	4.6	4.5	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.3	4.2	4.0	
			10.0	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.6	4.6	4.6	4.5	4.4	4.5	4.4	4.4	4.3	4.2	

