

# 屋内照明器具特性

品番 (品名)	LGB15108				
光源	LLD3000CU1 x1 795.0 lm				
管理番号	K0178732(0)DR1				
BZ分類	BZ5/0.7/BZ4/2.3/BZ5				

器具効率	53%	天井	80%				70%				50%				30%				0%			
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		51%		床	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM		
保守率	良	0.67	0.6	30	24	20	17	30	24	20	17	28	23	20	17	27	22	19	17	16		
	中	0.63	0.8	36	30	26	23	35	29	25	23	33	28	25	22	32	27	24	22	21		
	否	0.56	1.0	39	33	29	27	38	33	29	26	36	32	29	26	35	31	28	26	24		
			0.56	1.25	42	37	33	30	41	36	33	30	39	35	32	30	37	34	31	29	28	
下方投影面積			cm <sup>2</sup>		1.5	44	40	36	33	43	39	36	33	41	38	35	32	39	36	34	32	30
			cm <sup>2</sup>		2.0	47	43	40	37	46	42	40	37	44	41	39	36	42	40	38	36	34
取付高さ	器具間隔最大限				2.5	49	45	43	40	48	45	42	40	46	43	41	39	44	42	40	38	37
	横方向 (A)	縦方向 (B)			3.0	50	47	45	43	49	46	44	42	47	45	43	41	45	44	42	40	39
Hm	0.85Hm	0.85Hm			4.0	52	49	47	46	51	49	47	45	49	47	45	44	47	46	44	43	41
					5.0	53	51	49	47	52	50	48	47	50	48	47	46	48	47	46	45	43
					7.0	54	52	51	50	53	51	50	49	51	50	49	48	49	48	48	47	45
					10.0	55	54	53	52	54	53	52	51	52	51	50	50	50	49	48	48	46

