

屋内照明器具特性

品番 (品名)	LGB15108				
光源	LLD2000CU1 x1		566.0 lm		
管理番号	K0178733(0)DR1				
BZ分類	BZ5/0.7/BZ4/2.3/BZ5				

器具効率	64%	天井	80%				70%				50%				30%				0%																																									
	上方光束 3%		下方光束 61%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
				壁	10%				10%				10%				10%				0%																																							
床	室指数																				照明率 (X0.01)																				ZCM																			
保守率	良	0.67	0.6	37	29	24	21	36	29	24	21	34	28	24	21	33	27	23	20	19																																								
	中	0.63	0.8	43	36	31	27	42	35	31	27	40	34	30	27	38	33	29	27	25																																								
	否	0.56	1.0	47	40	36	32	46	40	35	32	44	38	34	31	42	37	34	31	29																																								
			1.25	51	45	40	37	49	44	40	36	47	42	39	36	45	41	38	35	34																																								
下方投影面積	c m ²		1.5	53	48	43	40	52	47	43	40	50	45	42	39	48	44	41	38	37																																								
	等価発光面積		c m ²	2.0	57	52	48	45	55	51	48	45	53	50	47	44	51	48	45	43	41																																							
取付高さ	器具間隔最大限		2.5	59	55	52	49	58	54	51	48	55	52	50	47	53	51	48	46	44																																								
	横方向 (A)	縦方向 (B)	3.0	60	57	54	51	59	56	53	51	57	54	52	50	55	52	51	49	47																																								
H m	0.85 H m	0.85 H m	4.0	62	59	57	55	61	59	56	54	59	57	55	53	57	55	53	52	50																																								
			5.0	63	61	59	57	62	60	58	57	60	58	57	55	58	57	55	54	52																																								
			7.0	65	63	61	60	64	62	61	59	61	60	59	58	59	58	57	56	54																																								
			10.0	66	65	63	62	65	64	62	61	63	62	61	60	61	60	59	58	56																																								

