

# 屋内照明器具特性

品番 (品名) **LGB15108**

光源 **LLD2020CU1 ×1** **468.0 lm**

管理番号 **K0178736(0)DR1**

BZ分類 **BZ1**

器具効率	60%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	60%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良 0.67	0.6	49	45	43	41	49	45	43	41	48	45	43	41	47	44	42	41	40	
	中 0.63	0.8	53	49	47	45	52	49	47	45	51	48	46	45	50	48	46	45	44	
	否 0.56	1.0	55	52	49	48	54	51	49	48	53	51	49	47	52	50	48	47	46	
下方投影面積	cm <sup>2</sup>	1.25	57	54	52	50	56	54	52	50	55	53	51	50	54	52	51	49	48	
		1.5	58	55	53	52	57	55	53	52	56	54	53	51	55	53	52	51	50	
等価発光面積	cm <sup>2</sup>	2.0	60	58	56	54	59	57	55	54	58	56	55	54	57	55	54	53	52	
		2.5	61	59	57	56	60	58	57	56	59	57	56	55	57	56	55	55	53	
取付高さ	器具間隔最大限		3.0	61	60	58	57	61	59	58	57	59	58	57	56	58	57	56	54	
	横方向 (A)	縦方向 (B)																		
Hm	0.46Hm	0.46Hm	4.0	62	61	60	59	61	60	59	58	60	59	58	58	59	58	57	56	
			5.0	63	62	61	60	62	61	60	59	61	60	59	59	59	59	58	58	56
			7.0	63	62	62	61	62	62	61	61	61	61	60	60	60	59	59	57	
			10.0	64	63	63	62	63	62	62	62	62	61	61	60	60	60	59	58	

