

屋内照明器具特性	
品番 (品名)	LGB15379
光源	LLD4000MLCE1 ×1 845.0 l m
管理番号	K0176223 (0) DR 1
BZ分類	BZ5

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	3 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	66 %																																																						
保守率	良 中 否	0.67	0.6	3.8	3.0	2.4	2.1	3.7	2.9	2.4	2.1	3.5	2.8	2.4	2.0	3.3	2.7	2.3	2.0	1.9																																			
		0.63	0.8	4.5	3.7	3.1	2.7	4.4	3.6	3.1	2.7	4.1	3.5	3.0	2.7	3.9	3.4	3.0	2.7	2.5																																			
			1.0	4.9	4.2	3.7	3.2	4.8	4.1	3.6	3.2	4.6	4.0	3.5	3.2	4.3	3.8	3.4	3.1	2.9																																			
		0.56	1.25	5.3	4.7	4.2	3.8	5.2	4.6	4.1	3.7	5.0	4.4	4.0	3.7	4.7	4.3	3.9	3.6	3.4																																			
下方投影面積	c m ²	1.5	5.6	5.0	4.5	4.1	5.5	4.9	4.5	4.1	5.2	4.7	4.4	4.0	5.0	4.6	4.2	4.0	3.8																																				
		2.0	6.0	5.5	5.1	4.7	5.9	5.4	5.0	4.7	5.6	5.2	4.9	4.6	5.4	5.0	4.7	4.5	4.3																																				
取付高さ	器具間隔最大限		2.5	6.3	5.8	5.4	5.1	6.1	5.7	5.4	5.1	5.9	5.5	5.2	5.0	5.6	5.3	5.1	4.9																																				
	横方向 (A)	縦方向 (B)	3.0	6.4	6.0	5.7	5.4	6.3	5.9	5.6	5.4	6.0	5.7	5.5	5.2	5.8	5.6	5.3	5.1																																				
H m	1.17 H m	1.17 H m	4.0	6.7	6.3	6.1	5.8	6.5	6.2	6.0	5.8	6.3	6.0	5.8	5.6	6.0	5.8	5.7	5.5																																				
			5.0	6.8	6.5	6.3	6.1	6.7	6.4	6.2	6.0	6.4	6.2	6.0	5.9	6.2	6.0	5.9	5.7																																				
			7.0	6.9	6.8	6.6	6.4	6.8	6.6	6.5	6.3	6.6	6.4	6.3	6.2	6.4	6.2	6.1	6.0																																				
			10.0	7.1	6.9	6.8	6.7	6.9	6.8	6.7	6.6	6.7	6.6	6.5	6.4	6.5	6.4	6.3	6.2																																				

