

屋内照明器具特性

品番 (品名)	LGB15379														
光源	LLD4000MLCB1 ×1 845.0 lm														
管理番号	K0176224(0)DR1														
BZ分類	BZ5														

器具効率	60%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 (X0.01)																ZCM		
下方光束	58%																				
保守率	良 中 否	0.67	0.6	3.4	2.6	2.1	1.8	3.3	2.6	2.1	1.8	3.1	2.5	2.1	1.8	2.9	2.4	2.0	1.8	1.6	
		0.63	0.8	3.9	3.2	2.8	2.4	3.8	3.2	2.7	2.4	3.6	3.1	2.7	2.4	3.5	3.0	2.6	2.3	2.2	
		0.56	1.0	4.3	3.7	3.2	2.9	4.2	3.6	3.2	2.8	4.0	3.5	3.1	2.8	3.8	3.4	3.0	2.7	2.6	
			1.25	4.7	4.1	3.6	3.3	4.6	4.0	3.6	3.3	4.4	3.9	3.5	3.2	4.2	3.7	3.4	3.2	3.0	
下方投影面積	c m ²	1.5	4.9	4.4	4.0	3.6	4.8	4.3	3.9	3.6	4.6	4.2	3.8	3.5	4.4	4.0	3.7	3.5	3.3		
		2.0	5.3	4.8	4.5	4.1	5.2	4.7	4.4	4.1	4.9	4.6	4.3	4.0	4.7	4.4	4.2	3.9	3.7		
取付高さ	器具間隔最大限		2.5	5.5	5.1	4.8	4.5	5.4	5.0	4.7	4.4	5.2	4.8	4.6	4.4	4.9	4.7	4.5	4.3		
	横方向 (A)	縦方向 (B)	3.0	5.7	5.3	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	5.1	4.9	4.7	4.5		
H m	1.17 H m	1.17 H m	4.0	5.8	5.6	5.3	5.1	5.7	5.5	5.3	5.1	5.5	5.3	5.1	4.9	5.3	5.1	5.0	4.8		
			5.0	6.0	5.7	5.5	5.3	5.9	5.6	5.5	5.3	5.6	5.5	5.3	5.2	5.4	5.3	5.2	5.0	4.8	
			7.0	6.1	5.9	5.8	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.5	5.4	5.6	5.5	5.4	5.3		
			10.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.6	5.7	5.6	5.5	5.2		

