

屋内照明器具特性

品番 (品名) **LGB15379**

光源 **LLD2020MLCE1 x1** **460.0lm**

管理番号 **K0176228(0)DR1**

BZ分類 **BZ1**

器具効率	89%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	89%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	70	64	60	57	70	64	60	57	68	63	59	57	67	62	59	57	56	
	中 0.63	0.8	76	70	67	64	75	70	66	64	74	69	66	63	72	68	65	63	62	
	否 0.56	1.0	80	75	71	68	79	74	71	68	77	73	70	68	76	72	69	67	66	
下方投影面積 等価発光面積	cm ²	1.25	83	78	75	72	82	78	75	72	80	77	74	71	79	76	73	71	70	
		1.5	85	81	78	75	84	80	77	75	82	79	76	74	81	78	76	74	72	
		2.0	88	85	82	79	87	84	81	79	85	82	80	78	83	81	79	77	76	
取付高さ	器具間隔最大限		2.5	90	87	84	82	89	86	84	82	87	84	82	81	85	83	81	80	78
	横方向 (A)	縦方向 (B)	3.0	91	88	86	84	90	87	85	84	88	86	84	83	86	84	83	82	80
Hm	0.50Hm	0.50Hm	4.0	92	90	88	87	91	89	88	86	89	88	86	85	87	86	85	84	82
			5.0	93	91	90	89	92	91	89	88	90	89	88	87	88	87	86	85	83
			7.0	94	93	92	91	93	92	91	90	91	90	89	88	89	88	88	87	85
			10.0	95	94	93	92	94	93	92	92	92	91	90	90	89	89	88	86	86

