

屋内照明器具特性	
品番 (品名)	LGB15379
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m
管理番号	K0184424 (0) DR1
BZ分類	BZ5

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	5 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	64 %																																																						
保守率	良 中 否	0.67	0.6	3.8	2.9	2.4	2.0	3.7	2.9	2.4	2.0	3.4	2.8	2.3	2.0	3.3	2.7	2.2	1.9	1.8																																			
		0.63	0.8	4.4	3.6	3.1	2.7	4.3	3.6	3.0	2.7	4.1	3.4	3.0	2.6	3.8	3.3	2.9	2.6	2.4																																			
		0.56	1.0	4.9	4.1	3.6	3.2	4.7	4.0	3.5	3.2	4.5	3.9	3.4	3.1	4.2	3.7	3.3	3.0	2.8																																			
			1.25	5.3	4.6	4.1	3.7	5.1	4.5	4.0	3.6	4.8	4.3	3.9	3.6	4.6	4.1	3.8	3.5	3.3																																			
下方投影面積	c m ²	1.5	5.6	4.9	4.4	4.1	5.4	4.8	4.4	4.0	5.1	4.6	4.2	3.9	4.8	4.4	4.1	3.8	3.6																																				
		2.0	5.9	5.4	5.0	4.6	5.8	5.3	4.9	4.5	5.5	5.1	4.7	4.4	5.2	4.9	4.6	4.3	4.1																																				
		2.5	6.2	5.7	5.3	5.0	6.0	5.6	5.2	4.9	5.7	5.4	5.1	4.8	5.4	5.2	4.9	4.7	4.4																																				
取付高さ	器具間隔最大限		H m	1.13 H m	1.13 H m	3.0	6.3	5.9	5.6	5.3	6.2	5.8	5.5	5.2	5.9	5.6	5.3	5.1	5.6	5.4	5.1	4.9	4.6																																
	4.0	6.6				6.2	5.9	5.7	6.4	6.1	5.8	5.6	6.1	5.9	5.6	5.4	5.8	5.6	5.4	5.3	5.0																																		
			5.0	6.7	6.4	6.2	5.9	6.6	6.3	6.1	5.9	6.3	6.1	5.9	5.7	6.0	5.8	5.7	5.5	5.2																																			
			7.0	6.9	6.7	6.5	6.3	6.7	6.5	6.3	6.2	6.4	6.3	6.1	6.0	6.2	6.0	5.9	5.8	5.5																																			
			10.0	7.0	6.8	6.7	6.5	6.8	6.7	6.6	6.4	6.6	6.4	6.3	6.2	6.3	6.2	6.1	6.0	5.7																																			

