

屋内照明器具特性

品番 (品名)	LGB15390		
光源	LLD3020LCE1 ×1	795.0 1m	
管理番号	K0176260(0)DR1		
BZ分類	BZ1		

器具効率	65%	天井	80%				70%				50%				30%				0%																																	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																																		
上方光束	0%	反射率	壁																	室指数	照明率 (X0.01)																ZCM															
下方光束	65%		床	10%				10%				10%				10%					10%																															
保守率	良 0.67	0.6	0.6	53	49	46	44	53	49	46	44	52	48	46	44	51	48	45	44	43																																
	中 0.63		0.8	57	53	51	49	57	53	50	49	56	52	50	48	55	52	50	48	47																																
	否 0.56		1.0	60	56	54	52	59	56	53	52	58	55	53	51	57	54	53	51	50																																
下方投影面積	cm ²	1.25	62	59	56	55	61	58	56	54	60	57	56	54	59	57	55	54	53																																	
			1.5	63	60	58	57	63	60	58	56	61	59	57	56	60	58	57	55	54																																
等価発光面積	cm ²	2.0	65	63	61	59	64	62	61	59	63	61	60	59	62	60	59	58	57																																	
			2.5	66	64	63	61	65	64	62	61	64	63	61	60	63	62	61	60	58																																
取付高さ	器具間隔最大限		3.0	67	65	64	63	66	65	63	62	65	64	62	61	64	62	62	61	59																																
	横方向 (A)	縦方向 (B)		4.0	68	67	65	64	67	66	65	64	66	65	64	63	64	64	63	62	61																															
Hm	0.49Hm	0.49Hm	5.0	68	67	66	66	68	67	66	65	66	65	65	64	65	64	64	63	62																																
			7.0	69	68	68	67	68	68	67	66	67	66	66	65	66	65	65	64	62																																
			10.0	70	69	68	68	69	68	68	67	67	67	67	66	66	65	65	65	63																																

