

屋内照明器具特性	
品番 (品名)	XAS1033L
光源	LED2700_70_400 ×1 400.0 lm
管理番号	K0170906(1)DB1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%					
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%					
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%				
下方光束	100%		床	10%				10%				10%				10%				0%				
		室指数	照明率 (X0.01)																ZCM					
保守率	良	0.67	0.6	85	80	76	73	85	79	76	73	83	79	76	73	82	78	75	73	72				
	中	0.63	0.8	91	86	82	80	90	85	82	80	89	85	82	80	87	84	81	79	78				
	否	0.56	1.0	94	90	87	84	94	89	86	84	92	88	86	84	91	87	85	83	82				
下方投影面積	cm ²	等価発光面積	cm ²	1.25	97	93	90	88	96	93	90	88	95	92	89	87	93	91	88	87	85			
				1.5	99	96	93	91	98	95	92	90	96	94	91	90	95	92	91	89	88			
取付高さ	器具間隔最大限		Hm	0.41Hm	0.41Hm	2.5	103	100	98	97	102	100	98	96	100	98	96	95	98	97	95	94	92	
	横方向 (A)	縦方向 (B)				3.0	104	102	100	98	103	101	99	98	101	99	98	97	99	98	96	95	93	
Hm	0.41Hm	0.41Hm	Hm	0.41Hm	Hm	4.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	95	
						5.0	106	104	103	102	105	103	102	101	102	101	101	100	100	100	99	98	96	96
Hm	0.41Hm	0.41Hm	Hm	0.41Hm	Hm	7.0	106	105	104	104	105	104	104	103	103	102	102	101	101	100	99	97		
						10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98	

