

屋内照明器具特性	
品番 (品名)	LGB15150
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m
管理番号	K0184435 (0) DR1
BZ分類	BZ4/8.5/BZ5

器具効率	43%	天井	80%				70%				50%				30%				0%		
	上方光束		1%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		42%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	2.6	2.1	1.8	1.6	2.5	2.1	1.8	1.6	2.4	2.0	1.7	1.6	2.3	2.0	1.7	1.5	1.5	
	中	0.63	0.8	3.0	2.5	2.2	2.0	2.9	2.5	2.2	2.0	2.8	2.4	2.2	2.0	2.7	2.4	2.1	1.9	1.8	
	否	0.56	1.0	3.2	2.8	2.5	2.3	3.2	2.8	2.5	2.3	3.0	2.7	2.4	2.2	2.9	2.6	2.4	2.2	2.1	
	下方投影面積	c m ²		1.25	3.5	3.1	2.8	2.6	3.4	3.0	2.8	2.6	3.3	3.0	2.7	2.5	3.1	2.9	2.7	2.5	2.4
取付高さ	器具間隔最大限		1.5	3.6	3.3	3.0	2.8	3.6	3.2	3.0	2.8	3.4	3.1	2.9	2.7	3.3	3.0	2.9	2.7	2.6	
	横方向 (A)	縦方向 (B)	2.0	3.9	3.6	3.3	3.1	3.8	3.5	3.3	3.1	3.6	3.4	3.2	3.0	3.5	3.3	3.1	3.0	2.9	
H m	0.98 H m	0.98 H m	2.5	4.0	3.7	3.5	3.3	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.3	3.6	3.5	3.3	3.2	3.1	
			3.0	4.1	3.9	3.7	3.5	4.0	3.8	3.6	3.5	3.9	3.7	3.5	3.4	3.7	3.6	3.5	3.3	3.2	
			4.0	4.2	4.0	3.9	3.7	4.1	4.0	3.8	3.7	4.0	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.4	
			5.0	4.3	4.1	4.0	3.9	4.2	4.1	4.0	3.8	4.1	4.0	3.8	3.8	3.9	3.8	3.8	3.7	3.5	
			7.0	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.0	4.2	4.1	4.0	3.9	4.0	4.0	3.9	3.8	3.7	
			10.0	4.4	4.4	4.3	4.2	4.4	4.3	4.2	4.2	4.2	4.2	4.1	4.1	4.1	4.0	4.0	4.0	3.8	

