

屋内照明器具特性

品番 (品名)	LGB15391	
光源	LLD3020MLCB1 ×1	715.0 lm
管理番号	K0176279(0)DR1	
BZ分類	BZ1	

器具効率	59%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	59%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	4.9	4.5	4.3	4.1	4.8	4.5	4.2	4.1	4.8	4.4	4.2	4.1	4.7	4.4	4.2	4.1	4.0	
	中 0.63		5.2	4.9	4.7	4.5	5.2	4.9	4.6	4.5	5.1	4.8	4.6	4.5	5.0	4.8	4.6	4.5	4.4	
	否 0.56		5.5	5.2	4.9	4.8	5.4	5.1	4.9	4.8	5.3	5.1	4.9	4.7	5.2	5.0	4.8	4.7	4.6	
下方投影面積	cm ²	1.25	5.6	5.4	5.2	5.0	5.6	5.3	5.1	5.0	5.5	5.3	5.1	5.0	5.4	5.2	5.1	4.9	4.8	
		1.5	5.8	5.5	5.3	5.2	5.7	5.5	5.3	5.2	5.6	5.4	5.3	5.1	5.5	5.3	5.2	5.1	5.0	
等価発光面積	cm ²	2.0	5.9	5.7	5.6	5.4	5.9	5.7	5.5	5.4	5.8	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.2	
		2.5	6.0	5.9	5.7	5.6	6.0	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.3	
取付高さ	器具間隔最大限		3.0	6.1	5.9	5.8	5.7	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.8	5.7	5.6	5.5	5.4
	横方向 (A)	縦方向 (B)																		
Hm	0.50Hm	0.50Hm	4.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.5	5.5
			5.0	6.2	6.1	6.0	6.0	6.2	6.1	6.0	5.9	6.0	6.0	5.9	5.8	5.9	5.9	5.8	5.7	5.6
			7.0	6.3	6.2	6.1	6.2	6.2	6.1	6.0	6.1	6.0	6.0	5.9	6.0	5.9	5.9	5.8	5.7	5.7
			10.0	6.3	6.3	6.2	6.2	6.3	6.2	6.2	6.1	6.1	6.1	6.0	6.0	6.0	5.9	5.9	5.8	5.8

