

屋内照明器具特性	
品番 (品名)	LGB15151
光源	LLD4000MLCB1 ×1                      845.0 l m
管理番号	K0176276 ( 0 ) DR 1
BZ分類	BZ4 / 6.0 / BZ5

器具効率	44 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	1 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	43 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	2.6	2.1	1.8	1.6	2.6	2.1	1.8	1.6	2.5	2.0	1.8	1.5	2.4	2.0	1.7	1.5	1.4			
	中	0.63	0.8	3.0	2.6	2.2	2.0	3.0	2.5	2.2	2.0	2.8	2.4	2.2	2.0	2.7	2.4	2.1	1.9	1.8			
	否	0.56	1.0	3.3	2.9	2.5	2.3	3.2	2.8	2.5	2.3	3.1	2.7	2.5	2.3	3.0	2.7	2.4	2.2	2.1			
			1.25	3.6	3.2	2.8	2.6	3.5	3.1	2.8	2.6	3.3	3.0	2.8	2.6	3.2	2.9	2.7	2.5	2.4			
下方投影面積			1.5	3.7	3.4	3.1	2.8	3.6	3.3	3.0	2.8	3.5	3.2	3.0	2.8	3.4	3.1	2.9	2.7	2.6			
			2.0	4.0	3.7	3.4	3.2	3.9	3.6	3.4	3.2	3.7	3.5	3.3	3.1	3.6	3.4	3.2	3.1	2.9			
取付高さ	器具間隔最大限		2.5	4.1	3.8	3.6	3.4	4.0	3.8	3.6	3.4	3.9	3.7	3.5	3.3	3.7	3.6	3.4	3.3	3.1			
	横方向 (A)	縦方向 (B)	3.0	4.2	4.0	3.8	3.6	4.1	3.9	3.7	3.6	4.0	3.8	3.6	3.5	3.8	3.7	3.6	3.4	3.3			
Hm	0.97Hm	0.97Hm	4.0	4.3	4.2	4.0	3.9	4.3	4.1	3.9	3.8	4.1	4.0	3.9	3.7	4.0	3.9	3.8	3.7	3.5			
			5.0	4.4	4.3	4.1	4.0	4.3	4.2	4.1	4.0	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.8	3.6			
			7.0	4.5	4.4	4.3	4.2	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.1	4.2	4.1	4.0	4.0	3.8			
			10.0	4.6	4.5	4.4	4.3	4.5	4.4	4.4	4.3	4.4	4.3	4.3	4.2	4.2	4.2	4.1	4.1	3.9			

