

# 屋内照明器具特性

品番 (品名)	LGB15151	
光源	LLD2000MLCE1 ×1	531.0 lm
管理番号	K0176277(0)DR1	
BZ分類	BZ4/6.0/BZ5	

器具効率	58%	天井	80%				70%				50%				30%				0%		
	上方光束		1%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		57%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.67	0.6	3.5	2.8	2.4	2.1	3.4	2.8	2.4	2.1	3.2	2.7	2.3	2.0	3.1	2.6	2.3	2.0	1.9	
	中	0.63	0.8	4.0	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.6	3.1	2.8	2.6	2.4	
	否	0.56	1.0	4.4	3.8	3.4	3.0	4.3	3.7	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	2.8	
	下方投影面積	c m <sup>2</sup>		1.25	4.7	4.2	3.8	3.4	4.6	4.1	3.7	3.4	4.4	4.0	3.6	3.4	4.2	3.9	3.6	3.3	3.2
取付高さ	器具間隔最大限		1.5	4.9	4.4	4.1	3.8	4.8	4.4	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.8	3.6	3.5	
	横方向 (A)	縦方向 (B)	2.0	5.2	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.0	3.9	
H m	0.97 H m		2.5	5.4	5.1	4.8	4.5	5.3	5.0	4.7	4.5	5.1	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.2	
	0.97 H m		3.0	5.6	5.3	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	5.1	4.9	4.7	4.5	4.4	
			4.0	5.7	5.5	5.3	5.1	5.6	5.4	5.2	5.0	5.4	5.2	5.1	4.9	5.3	5.1	5.0	4.8	4.6	
			5.0	5.8	5.6	5.4	5.3	5.7	5.5	5.4	5.2	5.5	5.4	5.2	5.1	5.4	5.2	5.1	5.0	4.8	
			7.0	6.0	5.8	5.7	5.5	5.9	5.7	5.6	5.5	5.7	5.6	5.4	5.3	5.5	5.4	5.3	5.2	5.0	
			10.0	6.0	5.9	5.8	5.7	6.0	5.9	5.8	5.7	5.8	5.7	5.6	5.5	5.6	5.5	5.5	5.4	5.2	

