

屋内照明器具特性

品番 (品名)	LGB15376														
光源	LLD4000LCB1 ×1 845.0 lm														
管理番号	K0176188(0)DR1														
BZ分類	BZ5														

器具効率	64%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	3%	室指数	照明率 (X0.01)															ZCM			
下方光束	61%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	35	27	22	19	34	27	22	18	32	26	21	18	30	25	21	18	16		
		0.8	41	34	29	25	40	33	28	25	38	32	28	24	36	31	27	24	22		
		1.0	45	38	33	30	44	38	33	29	42	36	32	29	40	35	31	28	26		
		1.25	49	43	38	34	48	42	38	34	45	40	36	33	43	39	35	33	31		
下方投影面積	c m ²	1.5	52	46	42	38	51	45	41	37	48	43	40	37	46	42	39	36	34		
		2.0	56	51	47	43	54	50	46	43	52	48	45	42	49	46	43	41	39		
取付高さ	器具間隔最大限		2.5	58	54	50	47	57	53	49	46	54	51	48	45	52	49	46	44	42	
	横方向 (A)	縦方向 (B)	3.0	60	56	53	50	58	55	52	49	56	53	50	48	53	51	49	47	44	
H m	1.17 H m	1.17 H m	4.0	62	59	56	54	60	58	55	53	58	55	53	52	55	54	52	50	48	
			5.0	63	60	58	56	62	59	57	55	59	57	55	54	57	55	54	52	50	
			7.0	64	62	61	59	63	61	60	58	61	59	58	57	58	57	56	55	52	
			10.0	66	64	63	62	64	63	62	61	62	61	60	59	60	59	58	57	54	

