

屋内照明器具特性	
品番 (品名)	XND2557WN
光源	LED5000_85_2415 ×1 2415.0lm
管理番号	K0176634(0)DB1
BZ分類	BZ1

器具効率	100 % 上方光束 0 % 下方光束 100 %	天井 反射率 壁 床 室指数	80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
			照明率 (X0.01) ZCM																
保守率	良 中 否 0.81 0.77 0.68	0.6	72	63	57	53	71	62	57	53	69	61	57	53	67	61	56	53	51
		0.8	81	73	68	64	80	73	68	64	78	72	67	64	76	71	67	64	62
		1.0	87	80	75	71	86	79	75	71	84	78	74	71	82	77	73	71	69
		1.25	91	85	81	77	90	85	80	77	88	83	80	77	86	82	79	76	75
下方投影面積 等価発光面積	cm ² cm ²	1.5	94	89	85	81	93	88	84	81	91	87	83	81	89	85	82	80	78
		2.0	98	93	90	87	96	93	89	87	94	91	88	86	92	89	87	85	83
		2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86
取付 高さ	器具間隔最大限		3.0	101	98	96	93	100	97	95	93	98	95	93	92	96	94	92	90
	横方向 (A)	縦方向 (B)	4.0	103	101	99	97	102	100	98	96	100	98	96	95	97	96	95	93
Hm	1.23Hm	1.23Hm	5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95
			7.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99

