

屋内照明器具特性

品番 (品名)	LGB15376														
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m														
管理番号	K0184422 (0) DR1														
BZ分類	BZ5														

器具効率	69 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	65 %																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.67 中 0.63 否 0.56	0.6	38	30	24	21	37	29	24	20	35	28	23	20	33	27	23	20	18	
		0.8	45	37	31	27	43	36	31	27	41	35	30	27	39	34	29	26	25	
		1.0	49	42	36	32	48	41	36	32	45	39	35	31	43	38	34	31	29	
		1.25	53	46	41	37	52	46	41	37	49	44	40	36	47	42	39	36	34	
下方投影面積	c m ²	1.5	56	50	45	41	55	49	44	41	52	47	43	40	49	45	42	39	37	
		2.0	60	55	50	47	58	54	50	46	56	52	48	45	53	50	47	44	42	
		2.5	62	58	54	51	61	57	53	50	58	55	52	49	56	53	50	48	45	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.13 H m	1.13 H m	3.0	64	60	57	54	63	59	56	53	60	57	54	52	57	55	52	50	48
			4.0	66	63	60	58	65	62	59	57	62	60	57	55	60	58	56	54	51
			5.0	67	65	62	60	66	64	61	59	63	61	60	58	61	59	58	56	54
			7.0	69	67	65	63	68	66	64	62	65	64	62	61	63	61	60	59	56
			10.0	70	69	67	66	69	68	66	65	66	65	64	63	64	63	62	61	58

