

# 屋内照明器具特性

|         |  |  |
|---------|--|--|
| 品番 (品名) | LGB15376                               |  |
| 光源      | LLD40402CQ1 (SHUKOU) ×1      620.0 1 m |  |
| 管理番号    | K0184423 (0) DR 1                      |  |
| BZ分類    | BZ1 / 1.8 / BZ2                        |  |

|        |               |                 |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |     |     |
|--------|---------------|-----------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|-----|-----|
| 器具効率   | 82 %          | 天井              | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |     |     |
|        | 上方光束          |                 | 2 %  | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10  | 0 % |     |
| 下方光束   | 80 %          | 床               | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |     |     |
| 室指数    | 照明率 ( X0.01 ) |                 |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |     | ZCM |
| 保守率    | 良             | 0.67            | 0.6  | 60 | 53 | 49 | 46   | 59 | 53 | 49 | 46   | 58 | 52 | 48 | 45   | 56 | 51 | 48 | 45  | 44  |     |
|        | 中             | 0.63            | 0.8  | 66 | 60 | 56 | 53   | 65 | 60 | 56 | 53   | 64 | 59 | 55 | 52   | 62 | 58 | 54 | 52  | 50  |     |
|        | 否             | 0.56            | 1.0  | 70 | 65 | 61 | 57   | 69 | 64 | 60 | 57   | 67 | 63 | 59 | 57   | 66 | 62 | 59 | 56  | 55  |     |
| 下方投影面積 | 等価発光面積        | cm <sup>2</sup> | 1.25 | 74 | 69 | 65 | 62   | 73 | 68 | 64 | 62   | 71 | 67 | 63 | 61   | 69 | 65 | 63 | 60  | 59  |     |
|        |               |                 | 1.5  | 76 | 71 | 68 | 65   | 75 | 71 | 67 | 65   | 73 | 69 | 66 | 64   | 71 | 68 | 65 | 63  | 61  |     |
| 取付高さ   | 器具間隔最大限       |                 | 2.5  | 81 | 78 | 75 | 73   | 80 | 77 | 74 | 72   | 77 | 75 | 73 | 71   | 75 | 73 | 71 | 70  | 68  |     |
|        | 横方向 (A)       | 縦方向 (B)         | 3.0  | 82 | 79 | 77 | 75   | 81 | 78 | 76 | 74   | 79 | 76 | 75 | 73   | 76 | 75 | 73 | 72  | 69  |     |
| Hm     | 0.72Hm        | 0.72Hm          | 4.0  | 84 | 81 | 79 | 78   | 82 | 80 | 79 | 77   | 80 | 78 | 77 | 76   | 78 | 77 | 75 | 74  | 72  |     |
|        |               |                 | 5.0  | 85 | 83 | 81 | 80   | 83 | 82 | 80 | 79   | 81 | 80 | 78 | 77   | 79 | 78 | 77 | 76  | 73  |     |
|        |               |                 | 7.0  | 86 | 84 | 83 | 82   | 85 | 83 | 82 | 81   | 82 | 81 | 80 | 79   | 80 | 79 | 78 | 78  | 75  |     |
|        |               |                 | 10.0 | 87 | 86 | 85 | 84   | 85 | 84 | 84 | 83   | 83 | 82 | 82 | 81   | 81 | 80 | 80 | 79  | 76  |     |

