

屋内照明器具特性

品番 (品名)	LGB15377				
光源	LLD4000LCE1 ×1 845.0 1 m				
管理番号	K0176229 (0) DR 1				
BZ分類	BZ5				

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	2 %																			
下方光束	51 %																			
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.0	2.4	2.0	1.7	2.9	2.4	2.0	1.7	2.8	2.3	1.9	1.7	2.7	2.2	1.9	1.7	1.5
	中	0.63	0.8	3.5	2.9	2.5	2.2	3.5	2.9	2.5	2.2	3.3	2.8	2.5	2.2	3.1	2.7	2.4	2.2	2.0
	否	0.56	1.0	3.9	3.3	2.9	2.6	3.8	3.3	2.9	2.6	3.6	3.2	2.8	2.6	3.4	3.1	2.8	2.5	2.4
			1.25	4.2	3.7	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	2.9	3.7	3.4	3.1	2.9	2.7
下方投影面積		c m ²	1.5	4.4	3.9	3.6	3.3	4.3	3.9	3.5	3.3	4.1	3.8	3.5	3.2	3.9	3.6	3.4	3.2	3.0
等価発光面積		c m ²	2.0	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.8	3.6	4.2	4.0	3.8	3.6	3.4
取付高さ	器具間隔最大限		2.5	4.9	4.6	4.3	4.0	4.8	4.5	4.2	4.0	4.6	4.3	4.1	3.9	4.4	4.2	4.0	3.8	3.7
	横方向 (A)	縦方向 (B)	3.0	5.0	4.7	4.5	4.3	4.9	4.6	4.4	4.2	4.7	4.5	4.3	4.1	4.5	4.4	4.2	4.0	3.9
H m	0.82 H m	0.82 H m	4.0	5.2	4.9	4.7	4.6	5.1	4.9	4.7	4.5	4.9	4.7	4.6	4.4	4.7	4.6	4.4	4.3	4.1
			5.0	5.3	5.1	4.9	4.8	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.3
			7.0	5.4	5.3	5.1	5.0	5.3	5.2	5.0	4.9	5.1	5.0	4.9	4.8	4.9	4.9	4.8	4.7	4.5
			10.0	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.2	5.1	5.1	5.0	5.0	5.0	4.9	4.9	4.6

