

屋内照明器具特性	
品番 (品名)	LGB15377
光源	LLD2000MLCE1 ×1 531.0 lm
管理番号	K0176240(0)DR1
BZ分類	BZ5

器具効率	62%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	60%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	35	28	23	20	34	28	23	20	33	27	23	20	31	26	22	19	18	
		0.8	41	34	30	26	40	34	29	26	38	33	29	26	37	32	28	25	24	
		1.0	45	39	34	31	44	38	34	31	42	37	33	30	40	36	32	30	28	
		1.25	49	43	39	35	48	42	38	35	46	41	37	35	44	40	37	34	32	
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	52	46	42	39	50	45	42	38	48	44	41	38	46	43	40	37	35	
		2.0	55	51	47	44	54	50	46	43	52	48	45	43	49	46	44	42	40	
		2.5	57	53	50	47	56	52	49	47	54	51	48	46	52	49	47	45	43	
取付 高さ	器具間隔最大限		3.0	59	55	52	50	57	54	52	49	55	53	50	48	53	51	49	47	45
	横方向 (A)	縦方向 (B)																		
H m	0.84 H m	0.84 H m	4.0	61	58	56	53	59	57	55	53	57	55	53	52	55	53	52	50	48
			5.0	62	60	58	56	61	59	57	55	58	57	55	54	56	55	54	52	50
			7.0	63	61	60	58	62	60	59	58	60	59	57	56	58	57	56	55	52
			10.0	64	63	62	61	63	62	61	60	61	60	59	58	59	58	57	57	54

