

屋内照明器具特性

品番 (品名)	LGB15377				
光源	LLD2000MLCB1 ×1 531.0 l m				
管理番号	K0176241 (0) DR 1				
BZ分類	BZ5				

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		2 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		61 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	3.6	2.8	2.4	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	2.0	3.2	2.6	2.2	2.0	1.8	
	中	0.63	0.8	4.2	3.5	3.0	2.7	4.1	3.4	3.0	2.6	3.9	3.3	2.9	2.6	3.7	3.2	2.9	2.6	2.4	
	否	0.56	1.0	4.6	4.0	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.1	3.6	3.3	3.0	2.9	
			1.25	5.0	4.4	3.9	3.6	4.9	4.3	3.9	3.6	4.6	4.2	3.8	3.5	4.4	4.0	3.7	3.4	3.3	
下方投影面積	c m ²		1.5	5.2	4.7	4.3	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.1	3.8	4.7	4.3	4.0	3.8	3.6	
	等価発光面積		c m ²	2.0	5.6	5.1	4.8	4.4	5.5	5.0	4.7	4.4	5.2	4.9	4.6	4.3	5.0	4.7	4.5	4.2	4.0
	取付高さ	器具間隔最大限		2.5	5.8	5.4	5.1	4.8	5.7	5.3	5.0	4.8	5.5	5.1	4.9	4.7	5.2	5.0	4.8	4.6	4.4
横方向 (A)		縦方向 (B)	3.0	6.0	5.6	5.3	5.1	5.8	5.5	5.3	5.0	5.6	5.3	5.1	4.9	5.4	5.2	5.0	4.8	4.6	
H m	0.84 H m	0.84 H m	4.0	6.1	5.9	5.6	5.4	6.0	5.8	5.6	5.4	5.8	5.6	5.4	5.2	5.6	5.4	5.3	5.1	4.9	
			5.0	6.3	6.0	5.8	5.7	6.2	5.9	5.8	5.6	5.9	5.8	5.6	5.5	5.7	5.6	5.4	5.3	5.1	
			7.0	6.4	6.2	6.1	5.9	6.3	6.1	6.0	5.9	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.3	
			10.0	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.1	6.0	5.9	6.0	5.9	5.8	5.8	5.5	

