

屋内照明器具特性

品番 (品名) **LGB15378**

光源 **LLD2020LCE1 x1** **460.0 l m**

管理番号 **K0176253(0)DR1**

BZ分類 **BZ1**

器具効率	80%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁																	
下方光束	80%		床	10%				10%				10%				10%				
		室指数	照明率 (X 0.01)																ZCM	
保守率	良	0.67	0.6	66	61	58	55	66	61	58	55	64	60	57	55	63	60	57	55	54
	中	0.63	0.8	71	66	63	61	70	66	63	61	69	65	62	60	68	64	62	60	59
	否	0.56	1.0	74	70	67	64	73	69	66	64	72	68	66	64	70	68	65	64	62
下方投影面積	等価発光面積	cm ²	1.25	76	73	70	68	76	72	69	67	74	71	69	67	73	70	68	67	65
			1.5	78	75	72	70	77	74	72	70	76	73	71	69	74	72	70	69	67
取付高さ	器具間隔最大限		2.5	82	79	77	76	81	79	77	75	79	77	76	74	77	76	75	73	72
	横方向 (A)	縦方向 (B)	3.0	82	80	79	77	82	80	78	77	80	78	77	76	78	77	76	75	73
Hm	0.46Hm	0.46Hm	4.0	84	82	81	79	83	81	80	79	81	80	79	78	79	78	77	77	75
			5.0	84	83	82	81	83	82	81	80	82	81	80	79	80	79	78	78	76
			7.0	85	84	83	82	84	83	82	82	82	82	81	80	81	80	80	79	77
			10.0	86	85	84	84	85	84	83	83	83	82	82	81	81	81	80	80	78

