

屋内照明器具特性

品番 (品名) **LGB15377**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0178729 (0) DR1**

BZ分類 **BZ1**

器具効率	54%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	54%		床	10%				10%				10%				10%				0%
		室指数	照明率 (×0.01)																ZCM	
保守率	良	0.67	0.6	4.4	4.0	3.8	3.6	4.3	4.0	3.8	3.6	4.2	3.9	3.8	3.6	4.2	3.9	3.7	3.6	3.5
	中	0.63	0.8	4.7	4.4	4.1	4.0	4.6	4.3	4.1	4.0	4.5	4.3	4.1	4.0	4.5	4.2	4.1	3.9	3.9
	否	0.56	1.0	4.9	4.6	4.4	4.2	4.8	4.6	4.4	4.2	4.7	4.5	4.3	4.2	4.6	4.4	4.3	4.2	4.1
下方投影面積	等価発光面積	cm ²	1.25	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.4	4.8	4.6	4.5	4.4	4.3
			1.5	5.2	4.9	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.6	4.9	4.8	4.6	4.5	4.4
取付高さ	器具間隔最大限		2.5	5.4	5.2	5.1	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.9	4.7
	横方向 (A)	縦方向 (B)	3.0	5.5	5.3	5.2	5.1	5.4	5.3	5.2	5.1	5.3	5.2	5.1	5.0	5.2	5.1	5.0	4.9	4.8
H _m	0.45H _m	0.45H _m	4.0	5.6	5.4	5.3	5.3	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.3	5.2	5.1	5.1	4.9
			5.0	5.6	5.5	5.4	5.4	5.5	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.3	5.2	5.2	5.0
			7.0	5.7	5.6	5.5	5.5	5.6	5.5	5.5	5.4	5.5	5.4	5.4	5.3	5.4	5.3	5.3	5.2	5.1
			10.0	5.7	5.6	5.6	5.6	5.6	5.5	5.5	5.5	5.5	5.5	5.4	5.4	5.4	5.4	5.3	5.3	5.2

