

屋内照明器具特性

品番 (品名) **LGB15378**

光源 **LLD3020MLCE1 ×1** 795.0 lm

管理番号 **K0176254(0)DR1**

BZ分類 **BZ1**

器具効率	63%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	63%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	52	48	45	43	51	47	45	43	50	47	45	43	50	47	45	43	42	
	中 0.63	0.8	55	52	49	47	55	51	49	47	54	51	49	47	53	50	48	47	46	
	否 0.56	1.0	58	54	52	50	57	54	52	50	56	53	51	50	55	53	51	50	49	
下方投影面積	cm ²	1.25	60	57	54	53	59	56	54	53	58	55	54	52	57	55	53	52	51	
		1.5	61	58	56	55	60	58	56	54	59	57	55	54	58	56	55	54	53	
等価発光面積	cm ²	2.0	63	60	59	57	62	60	58	57	61	59	58	56	60	58	57	56	55	
		2.5	64	62	60	59	63	61	60	59	62	60	59	58	60	59	58	57	56	
取付高さ	器具間隔最大限		3.0	64	63	61	60	64	62	61	60	62	61	60	59	61	60	59	57	
	横方向 (A)	縦方向 (B)	4.0	65	64	63	62	65	63	62	61	63	62	61	61	62	61	60	58	
Hm	0.46Hm	0.46Hm	5.0	66	65	64	63	65	64	63	63	64	63	62	62	62	61	61	59	
			7.0	66	66	65	64	66	65	64	64	64	64	63	63	63	63	62	60	
			10.0	67	66	66	65	66	66	65	65	65	64	64	64	63	63	63	61	

