

# 屋内照明器具特性

品番 (品名) **LGB15378**

光源 **LLD2020MLCE1 ×1**      **460.0 lm**

管理番号 **K0176256(0)DR1**

BZ分類 **BZ1**

器具効率	79%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁																	
下方光束	79%		床	10%				10%				10%				10%				
		室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.67	0.6	65	60	57	55	65	60	57	55	64	59	57	55	63	59	56	54	54
	中	0.63	0.8	70	65	62	60	69	65	62	60	68	64	62	60	67	64	61	59	58
	否	0.56	1.0	73	69	66	63	72	68	65	63	71	67	65	63	69	67	64	63	62
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	75	72	69	67	75	71	68	66	73	70	68	66	72	69	67	66	64
			1.5	77	74	71	69	76	73	71	69	75	72	70	68	73	71	69	68	66
取付高さ	器具間隔最大限		2.5	80	78	76	74	80	77	76	74	78	76	75	73	76	75	74	72	71
	横方向 (A)	縦方向 (B)	3.0	81	79	78	76	80	79	77	76	79	77	76	75	77	76	75	74	72
Hm	0.46Hm	0.46Hm	4.0	82	81	79	78	82	80	79	78	80	79	78	77	78	77	76	76	74
			5.0	83	82	81	80	82	81	80	79	81	80	79	78	79	78	77	77	75
			7.0	84	83	82	81	83	82	81	81	81	81	80	79	80	79	78	78	76
			10.0	84	84	83	83	84	83	82	82	82	81	81	80	80	80	79	79	77

