

屋内照明器具特性

品番 (品名)	LGB15378				
光源	LLD3000CU1 x1 795.0 lm				
管理番号	K0178732(0)DR1				
BZ分類	BZ5/0.7/BZ4/2.3/BZ5				

器具効率	53%	天井	80%				70%				50%				30%				0%		
	上方光束 2%		下方光束 51%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	3.0	2.4	2.0	1.7	3.0	2.4	2.0	1.7	2.8	2.3	2.0	1.7	2.7	2.2	1.9	1.7	1.6	
	中	0.63	0.8	3.6	3.0	2.6	2.3	3.5	2.9	2.5	2.3	3.3	2.8	2.5	2.2	3.2	2.7	2.4	2.2	2.1	
	否	0.56	1.0	3.9	3.3	2.9	2.7	3.8	3.3	2.9	2.6	3.6	3.2	2.9	2.6	3.5	3.1	2.8	2.6	2.4	
			0.56	1.25	4.2	3.7	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.7	3.4	3.1	2.9	2.8
下方投影面積			c m ²																		
			c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	0.85 H m	0.85 H m	4.0	5.2	4.9	4.7	4.6	5.1	4.9	4.7	4.5	4.9	4.7	4.5	4.4	4.7	4.6	4.4	4.3	4.1	
			5.0	5.3	5.1	4.9	4.7	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.3	
			7.0	5.4	5.2	5.1	5.0	5.3	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.9	4.8	4.8	4.7	4.5	
			10.0	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.2	5.1	5.0	5.0	5.0	5.0	4.9	4.8	4.6	

