

屋内照明器具特性

品番 (品名) **LGB15379**

光源 **LLD3020MLCB1 ×1** **715.0 lm**

管理番号 **K0176227(0)DR1**

BZ分類 **BZ1**

器具効率	71%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	71%	床		10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	56	51	48	46	56	51	48	46	55	50	48	45	54	50	47	45	45	
	中 0.63	0.8	61	56	53	51	60	56	53	51	59	55	53	51	58	55	52	50	49	
	否 0.56	1.0	64	60	57	54	63	59	56	54	62	58	56	54	61	58	56	54	53	
下方投影面積	cm ²	1.25	66	63	60	58	66	62	60	57	64	61	59	57	63	60	58	57	56	
		1.5	68	65	62	60	67	64	62	60	66	63	61	59	64	62	60	59	58	
等価発光面積	cm ²	2.0	70	68	65	63	70	67	65	63	68	66	64	62	67	65	63	62	61	
		2.5	72	69	67	66	71	69	67	65	69	67	66	65	68	66	65	64	62	
取付高さ	器具間隔最大限		3.0	73	71	69	67	72	70	68	67	70	69	67	66	69	67	66	65	64
	横方向 (A)	縦方向 (B)	4.0	74	72	71	69	73	71	70	69	71	70	69	68	70	69	68	67	65
Hm	0.50Hm	0.50Hm	5.0	74	73	72	71	74	72	71	70	72	71	70	69	70	70	69	68	66
			7.0	75	74	73	73	74	73	73	72	73	72	71	71	71	70	70	68	68
			10.0	76	75	74	74	75	74	74	73	73	73	72	72	71	71	71	69	69

