

屋内照明器具特性

品番 (品名) **LGB15379**

光源 **LLD2020CU1 ×1** **468.0 lm**

管理番号 **K0178725(0)DR1**

BZ分類 **BZ1**

器具効率	86%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	85%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	67	61	57	55	67	61	57	54	65	60	57	54	64	60	56	54	53	
	中 0.63	0.8	73	67	64	61	72	67	63	61	71	66	63	60	69	65	62	60	59	
	否 0.56	1.0	77	71	68	65	76	71	67	65	74	70	67	65	73	69	66	64	63	
下方投影面積	等価発光面積	cm ²	1.25	80	75	72	69	79	74	71	69	77	73	70	68	75	72	70	68	66
			2.0	84	81	78	76	83	80	78	75	81	79	77	75	80	78	76	74	72
取付高さ	器具間隔最大限		2.5	86	83	81	79	85	82	80	78	83	81	79	77	81	79	78	76	75
	横方向 (A)	縦方向 (B)	3.0	87	84	82	80	86	84	82	80	84	82	80	79	82	81	79	78	76
Hm	0.47Hm	0.47Hm	4.0	88	86	85	83	87	86	84	83	85	84	83	81	84	82	81	80	78
			5.0	89	88	86	85	88	87	85	84	86	85	84	83	84	83	82	82	80
			7.0	90	89	88	87	89	88	87	86	87	86	85	85	85	85	84	83	81
			10.0	91	90	89	88	90	89	88	88	88	87	87	86	86	85	85	82	82

