

# 屋内照明器具特性

|         |                                              |  |  |  |  |
|---------|----------------------------------------------|--|--|--|--|
| 品番 (品名) | LGB15379                                     |  |  |  |  |
| 光源      | LLD40001CQ1 ×1                      845.0 lm |  |  |  |  |
| 管理番号    | K0186490(0)DR1                               |  |  |  |  |
| BZ分類    | BZ5                                          |  |  |  |  |

|        |               |         |             |     |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |     |    |
|--------|---------------|---------|-------------|-----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|-----|----|
| 器具効率   | 66%           | 天井      | 80%         |     |     |    | 70% |    |     |    | 50% |    |     |    | 30% |    |     |    | 0% |     |    |
|        | 上方光束<br>2%    |         | 下方光束<br>64% | 反射率 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30 | 10  | 0% |
|        |               |         |             | 壁   | 10% |    |     |    | 10% |    |     |    | 10% |    |     |    | 10% |    |    |     | 0% |
| 室指数    | 照明率 ( X0.01 ) |         |             |     |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    | ZCM |    |
| 保守率    | 良             | 0.67    | 0.6         | 37  | 29  | 24 | 20  | 36 | 28  | 23 | 20  | 34 | 27  | 23 | 20  | 32 | 26  | 22 | 19 | 18  |    |
|        | 中             | 0.63    | 0.8         | 43  | 36  | 30 | 26  | 42 | 35  | 30 | 26  | 40 | 34  | 29 | 26  | 38 | 33  | 29 | 26 | 24  |    |
|        | 否             | 0.56    | 1.0         | 48  | 40  | 35 | 31  | 46 | 40  | 35 | 31  | 44 | 38  | 34 | 30  | 42 | 37  | 33 | 30 | 28  |    |
|        |               |         | 1.25        | 51  | 45  | 40 | 36  | 50 | 44  | 39 | 36  | 48 | 43  | 38 | 35  | 46 | 41  | 38 | 35 | 33  |    |
| 下方投影面積 |               |         | 1.5         | 54  | 48  | 43 | 40  | 53 | 47  | 43 | 39  | 50 | 46  | 42 | 39  | 48 | 44  | 41 | 38 | 36  |    |
|        |               |         | 2.0         | 58  | 53  | 49 | 45  | 57 | 52  | 48 | 45  | 54 | 50  | 47 | 44  | 52 | 48  | 46 | 43 | 41  |    |
| 取付高さ   | 器具間隔最大限       |         | 2.5         | 60  | 56  | 52 | 49  | 59 | 55  | 51 | 49  | 56 | 53  | 50 | 48  | 54 | 51  | 49 | 47 | 44  |    |
|        | 横方向 (A)       | 縦方向 (B) | 3.0         | 62  | 58  | 55 | 52  | 61 | 57  | 54 | 51  | 58 | 55  | 53 | 50  | 56 | 53  | 51 | 49 | 47  |    |
| Hm     | 1.12Hm        | 1.12Hm  | 4.0         | 64  | 61  | 58 | 56  | 63 | 60  | 57 | 55  | 60 | 58  | 56 | 54  | 58 | 56  | 54 | 53 | 50  |    |
|        |               |         | 5.0         | 65  | 63  | 61 | 58  | 64 | 62  | 60 | 58  | 62 | 60  | 58 | 56  | 60 | 58  | 56 | 55 | 53  |    |
|        |               |         | 7.0         | 67  | 65  | 63 | 62  | 66 | 64  | 62 | 61  | 63 | 62  | 61 | 59  | 61 | 60  | 59 | 58 | 55  |    |
|        |               |         | 10.0        | 68  | 67  | 65 | 64  | 67 | 66  | 64 | 63  | 65 | 64  | 63 | 62  | 63 | 62  | 61 | 60 | 57  |    |

