

屋内照明器具特性	
品番 (品名)	LGB15390
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176259(0)DR1
BZ分類	BZ4/2.3/BZ5

器具効率	63%	天井	80%				70%				50%				30%				0%				
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		61%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.67	0.6	3.7	3.0	2.5	2.2	3.6	3.0	2.5	2.2	3.5	2.9	2.5	2.2	3.3	2.8	2.4	2.2	2.0			
	中	0.63	0.8	4.3	3.6	3.1	2.8	4.2	3.6	3.1	2.8	4.0	3.5	3.1	2.8	3.8	3.4	3.0	2.7	2.6			
	否	0.56	1.0	4.7	4.0	3.6	3.2	4.6	4.0	3.5	3.2	4.4	3.9	3.5	3.2	4.2	3.8	3.4	3.1	3.0			
	下方投影面積	c m ²		1.25	5.0	4.5	4.0	3.7	4.9	4.4	4.0	3.6	4.7	4.3	3.9	3.6	4.5	4.1	3.8	3.6	3.4		
等価発光面積	c m ²		1.5	5.3	4.8	4.3	4.0	5.2	4.7	4.3	4.0	5.0	4.5	4.2	3.9	4.8	4.4	4.1	3.9	3.7			
	c m ²		2.0	5.6	5.2	4.8	4.5	5.5	5.1	4.7	4.5	5.3	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.1			
取付高さ	器具間隔最大限		H m	1.00 H m	1.00 H m	2.5	5.8	5.4	5.1	4.8	5.7	5.4	5.1	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	4.4
	横方向 (A)	縦方向 (B)				3.0	6.0	5.6	5.4	5.1	5.9	5.6	5.3	5.0	5.7	5.4	5.2	5.0	5.5	5.2	5.0	4.9	4.7
H m	H m		4.0	6.2	5.9	5.7	5.4	6.1	5.8	5.6	5.4	5.9	5.6	5.5	5.3	5.7	5.5	5.3	5.2	5.0			
	H m		5.0	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.8	5.6	5.5	5.8	5.6	5.5	5.4	5.2			
	H m		7.0	6.4	6.3	6.1	6.0	6.3	6.2	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.6	5.4			
	H m		10.0	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.1	6.0	6.0	6.0	6.0	5.9	5.8	5.6			

