

屋内照明器具特性

品番 (品名)	LGB15390				
光源	LLD2000MLCE1 ×1 531.0 l m				
管理番号	K0176265 (0) DR1				
BZ分類	BZ4/3.5/BZ5				

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
		床	10 %				10 %				10 %				10 %				0 %				
上方光束	2 %																						
下方光束	60 %																						
室指数	照明率 (X0.01)																			ZCM			
保守率	良 中 否	0.67	0.6	3.7	2.9	2.5	2.2	3.6	2.9	2.5	2.2	3.4	2.8	2.4	2.1	3.3	2.7	2.4	2.1	2.0			
		0.63	0.8	4.2	3.6	3.1	2.8	4.1	3.5	3.1	2.7	3.9	3.4	3.0	2.7	3.8	3.3	3.0	2.7	2.5			
		0.56	1.0	4.6	4.0	3.5	3.2	4.5	3.9	3.5	3.2	4.3	3.8	3.4	3.1	4.1	3.7	3.4	3.1	2.9			
			1.25	5.0	4.4	4.0	3.6	4.9	4.3	3.9	3.6	4.6	4.2	3.8	3.5	4.5	4.1	3.8	3.5	3.3			
下方投影面積	c m ²	1.5	5.2	4.7	4.3	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.1	3.9	4.7	4.3	4.0	3.8	3.6				
		2.0	5.5	5.1	4.7	4.4	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.3	5.0	4.7	4.5	4.3	4.1				
		2.5	5.8	5.4	5.1	4.8	5.6	5.3	5.0	4.7	5.4	5.1	4.9	4.6	5.2	5.0	4.8	4.6	4.4				
取付高さ	器具間隔最大限		H m	0.99 H m	0.99 H m	3.0	5.9	5.6	5.3	5.0	5.8	5.5	5.2	5.0	5.6	5.3	5.1	4.9	5.4	5.2	5.0	4.8	4.6
	4.0	6.1				5.8	5.6	5.4	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.2	5.6	5.4	5.2	5.1	4.9		
			5.0	6.2	6.0	5.8	5.6	6.1	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.7	5.5	5.4	5.3	5.1			
			7.0	6.3	6.2	6.0	5.9	6.2	6.1	5.9	5.8	6.0	5.9	5.8	5.7	5.8	5.7	5.6	5.5	5.3			
			10.0	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.9	5.9	5.8	5.7	5.5			

