

屋内照明器具特性

品番 (品名) **LGB15390**

光源 **LLD2020MLCE1 x1** **460.0lm**

管理番号 **K0176268(0)DR1**

BZ分類 **BZ1**

器具効率	82%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	82%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	66	61	58	55	66	61	57	55	65	60	57	55	64	60	57	55	54	
	中 0.63	0.8	71	67	63	61	71	66	63	61	69	66	63	61	68	65	62	60	59	
	否 0.56	1.0	75	70	67	65	74	70	67	65	72	69	66	64	71	68	66	64	63	
下方投影面積	cm ²	1.25	77	73	71	68	76	73	70	68	75	72	70	68	74	71	69	67	66	
		1.5	79	76	73	71	78	75	73	71	77	74	72	70	75	73	71	69	68	
等価発光面積	cm ²	2.0	81	79	76	74	80	78	76	74	79	77	75	73	77	75	74	73	71	
		2.5	83	80	78	77	82	80	78	76	80	78	77	75	79	77	76	75	73	
取付高さ	器具間隔最大限		3.0	84	82	80	78	83	81	79	78	81	79	78	77	79	78	77	76	74
	横方向 (A)	縦方向 (B)	4.0	85	83	82	80	84	82	81	80	82	81	80	79	80	79	79	78	76
H _m	0.5H _m	0.5H _m	5.0	86	84	83	82	85	83	82	81	83	82	81	80	81	80	80	79	77
			7.0	86	85	84	84	85	84	84	83	84	83	82	81	82	81	81	80	78
			10.0	87	86	86	85	86	85	85	84	84	84	83	83	82	82	82	81	79

