

屋内照明器具特性

品番 (品名)	LGB15390				
光源	LLD3000CU1 x1 795.0 lm				
管理番号	K0178737(0)DR1				
BZ分類	BZ4/2.3/BZ5				

器具効率	55%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	1%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	54%																																																						
保守率	良 中 否	0.67	0.6	3.3	2.6	2.2	1.9	3.2	2.6	2.2	1.9	3.0	2.5	2.2	1.9	2.9	2.5	2.1	1.9	1.8																																			
		0.63	0.8	3.8	3.2	2.8	2.5	3.7	3.1	2.7	2.4	3.5	3.0	2.7	2.4	3.4	2.9	2.6	2.4	2.3																																			
		0.56	1.0	4.1	3.5	3.1	2.8	4.0	3.5	3.1	2.8	3.8	3.4	3.0	2.8	3.7	3.3	3.0	2.7	2.6																																			
			1.25	4.4	3.9	3.5	3.2	4.3	3.8	3.5	3.2	4.1	3.7	3.4	3.2	4.0	3.6	3.3	3.1	3.0																																			
下方投影面積		cm ²																																																					
等価発光面積		cm ²																																																					
取付高さ	器具間隔最大限																																																						
	横方向 (A)	縦方向 (B)																																																					
Hm	1.00Hm	1.00Hm	4.0	5.4	5.2	5.0	4.8	5.3	5.1	4.9	4.7	5.1	4.9	4.8	4.6	5.0	4.8	4.7	4.5	4.4																																			
			5.0	5.5	5.3	5.1	5.0	5.4	5.2	5.1	4.9	5.2	5.1	4.9	4.8	5.1	4.9	4.8	4.7	4.5																																			
			7.0	5.6	5.5	5.3	5.2	5.5	5.4	5.3	5.2	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	4.7																																			
			10.0	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.4	5.5	5.4	5.3	5.2	5.3	5.2	5.2	5.1	4.9																																			

