

# 屋内照明器具特性

|         |                |          |
|---------|----------------|----------|
| 品番 (品名) | LGB15391       |          |
| 光源      | LLD3020LCE1 ×1 | 795.0 lm |
| 管理番号    | K0176272(0)DR1 |          |
| BZ分類    | BZ1            |          |

|        |                 |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率   | 65%             | 天井      | 80%  |     |    |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0% |     |
|        | 上方光束<br>0%      |         | 壁    | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束   | 65%             | 床       |      | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |    | 0%  |
| 室指数    | 照明率 (X0.01)     |         |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    | ZCM |
| 保守率    | 良 0.67          | 0.6     | 54   | 49  | 47 | 45 | 53  | 49  | 47 | 45 | 52  | 49  | 46 | 45 | 51  | 48  | 46 | 45 | 44 |     |
|        | 中 0.63          |         | 58   | 54  | 51 | 49 | 57  | 54  | 51 | 49 | 56  | 53  | 51 | 49 | 55  | 52  | 50 | 49 | 48 |     |
|        | 否 0.56          |         | 60   | 57  | 54 | 52 | 59  | 56  | 54 | 52 | 58  | 56  | 54 | 52 | 57  | 55  | 53 | 52 | 51 |     |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 62   | 59  | 57 | 55 | 61  | 59  | 57 | 55 | 60  | 58  | 56 | 55 | 59  | 57  | 56 | 54 | 53 |     |
|        |                 | 1.5     | 64   | 61  | 59 | 57 | 63  | 60  | 58 | 57 | 62  | 59  | 58 | 56 | 60  | 59  | 57 | 56 | 55 |     |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 65   | 63  | 61 | 60 | 65  | 63  | 61 | 59 | 63  | 62  | 60 | 59 | 62  | 61  | 59 | 58 | 57 |     |
|        |                 | 2.5     | 66   | 64  | 63 | 62 | 66  | 64  | 62 | 61 | 64  | 63  | 62 | 61 | 63  | 62  | 61 | 60 | 59 |     |
| 取付高さ   | 器具間隔最大限         |         | 3.0  | 67  | 65 | 64 | 63  | 66  | 65 | 64 | 62  | 65  | 64 | 63 | 62  | 64  | 63 | 62 | 61 | 60  |
|        | 横方向 (A)         | 縦方向 (B) |      | 4.0 | 68 | 67 | 66  | 65  | 67 | 66 | 65  | 64  | 66 | 65 | 64  | 63  | 65 | 64 | 63 | 62  |
| Hm     | 0.47Hm          | 0.47Hm  | 5.0  | 69  | 68 | 67 | 66  | 68  | 67 | 66 | 65  | 66  | 66 | 65 | 64  | 65  | 64 | 64 | 63 | 62  |
|        |                 |         | 7.0  | 69  | 68 | 68 | 67  | 68  | 68 | 67 | 66  | 67  | 66 | 66 | 65  | 66  | 65 | 65 | 64 | 63  |
|        |                 |         | 10.0 | 70  | 69 | 69 | 68  | 69  | 68 | 68 | 67  | 67  | 67 | 67 | 66  | 66  | 65 | 65 | 64 | 63  |

