

屋内照明器具特性

品番 (品名)	LGB15391														
光源	LLD2000MLCE1 ×1 531.0 lm														
管理番号	K0176277(0)DR1														
BZ分類	BZ4/6.0/BZ5														

器具効率	58%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	1%																			
下方光束	57%																			
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	3.5	2.8	2.4	2.1	3.4	2.8	2.4	2.1	3.2	2.7	2.3	2.0	3.1	2.6	2.3	2.0	1.9
	中	0.63	0.8	4.0	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.7	3.2	2.9	2.6	3.6	3.1	2.8	2.6	2.4
	否	0.56	1.0	4.4	3.8	3.4	3.0	4.3	3.7	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	2.8
			1.25	4.7	4.2	3.8	3.4	4.6	4.1	3.7	3.4	4.4	4.0	3.6	3.4	4.2	3.9	3.6	3.3	3.2
下方投影面積	cm ²		1.5	4.9	4.4	4.1	3.8	4.8	4.4	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.8	3.6	3.5
等価発光面積	cm ²		2.0	5.2	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.0	3.9
取付高さ	器具間隔最大限		2.5	5.4	5.1	4.8	4.5	5.3	5.0	4.7	4.5	5.1	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.2
	横方向 (A)	縦方向 (B)	3.0	5.6	5.3	5.0	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	5.1	4.9	4.7	4.5	4.4
H _m	0.97H _m	0.97H _m	4.0	5.7	5.5	5.3	5.1	5.6	5.4	5.2	5.0	5.4	5.2	5.1	4.9	5.3	5.1	5.0	4.8	4.6
			5.0	5.8	5.6	5.4	5.3	5.7	5.5	5.4	5.2	5.5	5.4	5.2	5.1	5.4	5.2	5.1	5.0	4.8
			7.0	6.0	5.8	5.7	5.5	5.9	5.7	5.6	5.5	5.7	5.6	5.4	5.3	5.5	5.4	5.3	5.2	5.0
			10.0	6.0	5.9	5.8	5.7	6.0	5.9	5.8	5.7	5.8	5.7	5.6	5.5	5.6	5.5	5.5	5.4	5.2

