

# 屋内照明器具特性

品番 (品名) **LGB15391**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0178745(0)DR1**

BZ分類 **BZ1**

器具効率	54%	天井	80%				70%				50%				30%				0%
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	54%	床	10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																
保守率	良 0.67	0.6	44	41	38	37	44	40	38	37	43	40	38	37	42	40	38	37	36
	中 0.63	0.8	47	44	42	40	47	44	42	40	46	43	42	40	45	43	41	40	39
	否 0.56	1.0	49	46	44	43	49	46	44	43	48	46	44	43	47	45	44	42	42
下方投影面積	cm <sup>2</sup>	1.25	51	48	47	45	50	48	46	45	49	47	46	45	48	47	45	44	44
		1.5	52	50	48	47	51	49	48	47	50	49	47	46	49	48	47	46	45
等価発光面積	cm <sup>2</sup>	2.0	53	52	50	49	53	51	50	49	52	50	49	48	51	50	49	48	47
		2.5	54	53	52	50	54	52	51	50	53	51	50	50	52	51	50	49	48
取付高さ	器具間隔最大限		3.0	55	54	52	51	54	53	52	51	53	52	51	51	52	51	51	49
	横方向 (A)	縦方向 (B)	4.0	56	55	54	53	55	54	53	53	54	53	52	52	53	52	52	51
Hm	0.47Hm	0.47Hm	5.0	56	55	55	54	56	55	54	53	54	54	53	53	53	53	52	51
			7.0	57	56	55	55	56	55	55	54	55	54	54	54	54	54	53	53
			10.0	57	57	56	56	56	56	55	55	55	55	54	54	54	53	52	

