

屋内照明器具特性

品番 (品名)	XLGB1102	
光源	LLD4000LCE1 ×1	845.0 lm
管理番号	K0176245(0)DR1	
BZ分類	BZ5/0.7/BZ4/2.3/BZ5	

器具効率	51%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		49%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	2.9	2.3	1.9	1.7	2.9	2.3	1.9	1.7	2.7	2.2	1.9	1.6	2.6	2.2	1.9	1.6	1.5	
	中	0.63	0.8	3.4	2.9	2.5	2.2	3.3	2.8	2.4	2.2	3.2	2.7	2.4	2.1	3.0	2.6	2.3	2.1	2.0	
	否	0.56	1.0	3.7	3.2	2.8	2.6	3.7	3.2	2.8	2.5	3.5	3.1	2.7	2.5	3.3	3.0	2.7	2.5	2.3	
			1.25	4.0	3.6	3.2	2.9	3.9	3.5	3.2	2.9	3.8	3.4	3.1	2.9	3.6	3.3	3.0	2.8	2.7	
下方投影面積	c m ²		1.5	4.2	3.8	3.5	3.2	4.1	3.7	3.4	3.2	4.0	3.6	3.3	3.1	3.8	3.5	3.3	3.1	2.9	
	等価発光面積		c m ²	2.0	4.5	4.2	3.9	3.6	4.4	4.1	3.8	3.6	4.2	4.0	3.7	3.5	4.1	3.8	3.6	3.4	3.3
取付高さ	器具間隔最大限		2.5	4.7	4.4	4.1	3.9	4.6	4.3	4.1	3.9	4.4	4.2	4.0	3.8	4.2	4.0	3.9	3.7	3.5	
	横方向 (A)	縦方向 (B)	3.0	4.8	4.5	4.3	4.1	4.7	4.5	4.2	4.1	4.5	4.3	4.1	4.0	4.4	4.2	4.0	3.9	3.7	
H m	0.85 H m	0.85 H m	4.0	5.0	4.7	4.6	4.4	4.9	4.7	4.5	4.3	4.7	4.5	4.4	4.2	4.5	4.4	4.3	4.1	4.0	
			5.0	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.8	4.7	4.5	4.4	4.6	4.5	4.4	4.3	4.1	
			7.0	5.2	5.0	4.9	4.8	5.1	5.0	4.8	4.7	4.9	4.8	4.7	4.6	4.8	4.7	4.6	4.5	4.3	
			10.0	5.3	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.0	4.9	4.9	4.8	4.8	4.8	4.7	4.7	4.5	

