

屋内照明器具特性	
品番 (品名)	LGB16702
光源	LLD2000CU1 x1 566.0 lm
管理番号	K0179083(0)DR1
BZ分類	BZ1

器具効率	55%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	55%																																																						
保守率	良 中 否 0.67 0.63 0.56	0.6	4.2	3.8	3.6	3.4	4.2	3.8	3.5	3.4	4.1	3.8	3.5	3.4	4.0	3.7	3.5	3.4	3.3																																				
		0.8	4.6	4.3	4.0	3.9	4.6	4.3	4.0	3.8	4.5	4.2	4.0	3.8	4.4	4.2	4.0	3.8	3.7																																				
		1.0	4.9	4.6	4.3	4.2	4.8	4.5	4.3	4.2	4.7	4.5	4.3	4.1	4.6	4.4	4.3	4.1	4.0																																				
		1.25	5.1	4.8	4.6	4.4	5.1	4.8	4.6	4.4	4.9	4.7	4.5	4.4	4.8	4.7	4.5	4.4	4.3																																				
下方投影面積	c m ²	1.5	5.2	5.0	4.8	4.6	5.2	5.0	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.6	4.5																																				
		2.0	5.4	5.2	5.1	4.9	5.4	5.2	5.0	4.9	5.2	5.1	5.0	4.8	5.1	5.0	4.9	4.8	4.7																																				
取付高さ	器具間隔最大限		2.5	5.5	5.4	5.2	5.1	5.5	5.3	5.2	5.1	5.3	5.2	5.1	5.0	5.2	5.1	5.0	4.8																																				
	横方向 (A)	縦方向 (B)	3.0	5.6	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.3	5.2	5.1	4.9																																				
H m	0.70 H m	0.70 H m	4.0	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.3	5.4	5.3	5.2	5.1																																				
			5.0	5.7	5.6	5.5	5.5	5.7	5.6	5.5	5.4	5.5	5.5	5.4	5.3	5.4	5.4	5.3	5.3	5.1																																			
			7.0	5.8	5.7	5.6	5.6	5.7	5.7	5.6	5.5	5.6	5.5	5.5	5.5	5.5	5.4	5.4	5.2																																				
			10.0	5.8	5.8	5.7	5.7	5.8	5.7	5.7	5.6	5.6	5.6	5.5	5.5	5.5	5.5	5.4	5.3																																				

