

屋内照明器具特性	
品番 (品名)	LGB16703
光源	LLD4000MLCE1 ×1 845.0 l m
管理番号	K0175764 (0) DR 1
BZ分類	BZ1

器具効率	27 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	27 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	2.5	2.4	2.3	2.3	2.5	2.4	2.3	2.3	2.4	2.4	2.3	2.3	2.4	2.3	2.3	2.3	2.2			
	中	0.63	0.8	2.6	2.5	2.4	2.4	2.5	2.5	2.4	2.4	2.5	2.4	2.4	2.4	2.5	2.4	2.4	2.4	2.3			
	否	0.56	1.0	2.6	2.5	2.5	2.4	2.6	2.5	2.5	2.4	2.6	2.5	2.5	2.4	2.5	2.5	2.5	2.4	2.4			
			1.25	2.7	2.6	2.5	2.5	2.6	2.6	2.5	2.5	2.6	2.6	2.5	2.5	2.6	2.5	2.5	2.5	2.4			
下方投影面積	c m ²	1.5	2.7	2.6	2.6	2.5	2.7	2.6	2.6	2.5	2.6	2.6	2.6	2.5	2.6	2.6	2.5	2.5	2.5	2.5			
		2.0	2.7	2.7	2.6	2.6	2.7	2.7	2.6	2.6	2.7	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.5	2.5			
取付高さ	器具間隔最大限		2.5	2.8	2.7	2.7	2.6	2.7	2.7	2.7	2.6	2.7	2.7	2.6	2.6	2.6	2.6	2.6	2.6	2.5			
	横方向 (A)	縦方向 (B)	3.0	2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6	2.6	2.7	2.6	2.6	2.6	2.5			
H m	0.76 H m	0.76 H m	4.0	2.8	2.8	2.7	2.7	2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6	2.6			
			5.0	2.8	2.8	2.8	2.7	2.8	2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6	2.6			
			7.0	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6			
			10.0	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6			

