

屋内照明器具特性

品番 (品名)	XL553WATC				
光源	LED3000_85_1430 x1 1430.0 lm				
管理番号	K0130716(2)DB1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
		床	10%				10%				10%				10%				0%			
上方光束	0%																					
下方光束	100%																					
		室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否	0.81	0.6	5.7	4.5	3.7	3.1	5.6	4.4	3.7	3.1	5.3	4.3	3.6	3.1	5.1	4.2	3.6	3.1	2.9		
		0.77	0.8	6.7	5.6	4.8	4.2	6.6	5.5	4.7	4.2	6.3	5.3	4.7	4.2	6.0	5.2	4.6	4.1	3.9		
		0.68	1.0	7.4	6.3	5.5	5.0	7.2	6.2	5.5	4.9	6.9	6.1	5.4	4.9	6.7	5.9	5.3	4.9	4.7		
			1.25	8.0	7.0	6.3	5.7	7.8	6.9	6.2	5.7	7.5	6.7	6.1	5.7	7.2	6.6	6.0	5.6	5.4		
下方投影面積		cm ²																				
等価発光面積		cm ²																				
取付高さ	器具間隔最大限																					
	横方向 (A)	縦方向 (B)																				
Hm	1.28Hm	1.28Hm																				
			4.0	9.8	9.4	9.0	8.7	9.7	9.3	9.0	8.6	9.4	9.1	8.8	8.5	9.2	8.9	8.6	8.4	8.1		
			5.0	10.0	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.3	9.1	8.9	9.4	9.1	8.9	8.7	8.4		
			7.0	10.3	10.0	9.7	9.5	10.1	9.9	9.6	9.4	9.9	9.6	9.5	9.3	9.6	9.4	9.3	9.1	8.8		
			10.0	10.4	10.2	10.1	9.9	10.3	10.1	9.9	9.8	10.0	9.9	9.7	9.6	9.8	9.7	9.6	9.4	9.2		

