

屋内照明器具特性

品番 (品名)	NNF 50911				
光源	LED4000_85_3260 x1 3260.0 1m				
管理番号	K0172825(0)DR1				
BZ分類	BZ6				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		20%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		80%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19	
	中	0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26	
	否	0.77	1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31	
	下方投影面積	c m ²		1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37
取付高さ	器具間隔最大限		2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47	
	横方向 (A)	縦方向 (B)																			
1.5m	2.2m	1.97m	2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
2	2.9	2.54	3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
2.5	3.61	3.12	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
3	4.33	3.72	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62	
			7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66	
			10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69	

