

# 屋内照明器具特性

品番 (品名)	LGB15391				
光源	LLD40001CQ1 ×1                      845.0 1m				
管理番号	K0186484 (0) DR1				
BZ分類	BZ5/0.7/BZ4/2.3/BZ5				

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束 下方光束	1 % 46 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	27	22	18	16	27	21	18	15	25	21	18	15	24	20	17	15	14	
		0.8	32	26	23	20	31	26	23	20	30	25	22	20	28	25	22	20	19	
		1.0	35	30	26	24	34	29	26	24	32	28	26	23	31	28	25	23	22	
		1.25	38	33	30	27	37	33	29	27	35	32	29	27	34	31	28	26	25	
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	39	35	32	30	39	35	32	29	37	34	31	29	35	33	30	29	27	
		2.0	42	39	36	34	41	38	35	33	39	37	35	33	38	36	34	32	31	
		2.5	44	41	38	36	43	40	38	36	41	39	37	35	39	38	36	34	33	
取付高さ H m	器具間隔最大限		3.0	45	42	40	38	44	42	39	38	42	40	38	37	41	39	38	36	35
	横方向 (A)	縦方向 (B)																		
	0.85 H m	0.85 H m	4.0	46	44	42	41	45	43	42	40	44	42	41	39	42	41	40	39	37
			5.0	47	45	44	42	46	45	43	42	45	43	42	41	43	42	41	40	38
			7.0	48	47	46	45	47	46	45	44	46	45	44	43	44	43	43	42	40
			10.0	49	48	47	46	48	47	46	46	46	45	44	45	44	44	43	42	

