

# 屋内照明器具特性

品番 (品名)	XLGB1401	
光源	LLD4000VCE1 ×1	845.0 lm
管理番号	K0176189(0)DR1	
BZ分類	BZ5	

器具効率	71%	天井	80%				70%				50%				30%				0%	
	上方光束 4%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	67%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	3.9	3.0	2.5	2.1	3.8	3.0	2.4	2.1	3.6	2.9	2.4	2.0	3.4	2.8	2.3	2.0	1.8
	中	0.63	0.8	4.6	3.8	3.2	2.8	4.5	3.7	3.1	2.8	4.2	3.6	3.1	2.7	4.0	3.4	3.0	2.7	2.5
	否	0.56	1.0	5.1	4.3	3.7	3.3	4.9	4.2	3.7	3.3	4.7	4.0	3.6	3.2	4.4	3.9	3.5	3.1	2.9
			1.25	5.5	4.8	4.2	3.8	5.3	4.7	4.2	3.8	5.1	4.5	4.1	3.7	4.8	4.3	3.9	3.6	3.4
下方投影面積	cm <sup>2</sup>		1.5	5.8	5.1	4.6	4.2	5.6	5.0	4.5	4.2	5.3	4.8	4.4	4.1	5.1	4.7	4.3	4.0	3.8
等価発光面積	cm <sup>2</sup>		2.0	6.2	5.6	5.2	4.8	6.0	5.5	5.1	4.8	5.7	5.3	5.0	4.6	5.5	5.1	4.8	4.5	4.3
取付高さ	器具間隔最大限		2.5	6.4	6.0	5.6	5.2	6.3	5.9	5.5	5.2	6.0	5.6	5.3	5.0	5.7	5.4	5.2	4.9	4.7
	横方向 (A)	縦方向 (B)	3.0	6.6	6.2	5.8	5.5	6.5	6.1	5.8	5.5	6.2	5.9	5.6	5.3	5.9	5.7	5.4	5.2	4.9
Hm	1.17Hm	1.17Hm	4.0	6.8	6.5	6.2	6.0	6.7	6.4	6.1	5.9	6.4	6.2	5.9	5.7	6.2	6.0	5.8	5.6	5.3
			5.0	7.0	6.7	6.5	6.2	6.8	6.6	6.4	6.2	6.6	6.4	6.2	6.0	6.3	6.1	6.0	5.8	5.5
			7.0	7.2	6.9	6.8	6.6	7.0	6.8	6.6	6.5	6.8	6.6	6.4	6.3	6.5	6.4	6.2	6.1	5.8
			10.0	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.7	6.9	6.8	6.7	6.6	6.6	6.5	6.5	6.4	6.1

