

屋内照明器具特性

品番 (品名)	XLGB1101	
光源	LLD4000VCE1 ×1	845.0 lm
管理番号	K0176229(0)DR1	
BZ分類	BZ5	

器具効率	53%	天井	80%				70%				50%				30%				0%		
	上方光束 2%		下方光束 51%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	中 否 0.63	0.6	30	24	20	17	29	24	20	17	28	23	19	17	27	22	19	17	15	
	1.0		39	33	29	26	38	33	29	26	36	32	28	26	34	31	28	25	24		
	1.25		42	37	33	30	41	36	33	30	39	35	32	29	37	34	31	29	27		
	1.5		44	39	36	33	43	39	35	33	41	38	35	32	39	36	34	32	30		
下方投影面積 等価発光面積	c m ²		2.0	47	43	40	37	46	42	39	37	44	41	38	36	42	40	38	36	34	
	c m ²		2.5	49	46	43	40	48	45	42	40	46	43	41	39	44	42	40	38	37	
取付高さ	器具間隔最大限		3.0	50	47	45	43	49	46	44	42	47	45	43	41	45	44	42	40	39	
	H m	0.82 H m	0.82 H m	4.0	52	49	47	46	51	49	47	45	49	47	46	44	47	46	44	43	41
			5.0	53	51	49	48	52	50	48	47	50	48	47	46	48	47	46	45	43	
			7.0	54	53	51	50	53	52	50	49	51	50	49	48	49	49	48	47	45	
			10.0	55	54	53	52	54	53	52	51	52	51	51	50	50	50	49	49	46	

